

LTE Modem Cards



LTE Advanced Cat 1, Cat 3 and Cat 6 Solutions



RLS Monitoring (Jamming Detection)



2G /3G Fallback Variants



GPS/A-GPS/GLONASS*



USB 2.0 Compatible



SIM card holder



Incremental FOTA



Plug & Play, fits 52-pin express socket



JAVA Embedded*



**) Depending on product variant*

Cinterion 4G Modem Cards

Global LTE Cat 1, Cat 3 and Cat 6 Connectivity for Industrial Solutions

Cinterion LTE Modem Cards

Global Connectivity in LTE Cat 1, Cat 3 and Cat 6 Product Variants

Gemalto Cinterion® LTE Modem Cards deliver instant access to cellular networks offering LTE Cat 1, Cat 3, and Cat 6 connectivity with optional 2G / 3G fallback when needed.

The devices are very easy to integrate by simply plugging into an existing 52-pin express card slot. They leverage a variety of Cinterion IoT Modules to meet the diverse needs of industrial solutions. These range from highly efficient LTE Cat 1 with IoT optimized speeds of 10Mbit/s download and 5Mbit/s uplink for applications not dependent on speed, all the way to high performance LTE Cat 6 enabling sizzling data speeds of 300 Mbit/s download and 50 Mbit/s uplink for advanced solutions including industrial routers, kiosk systems and video surveillance applications.

Three Product Variants Have Got You Covered. Globally.

Cinterion LTE Modem Cards provide global coverage and reliability from three product variants:

The Cinterion mPLS62 Modem Card delivers global connectivity from a single device, featuring 12 Band FDD-LTE, seven Band 3G HSPA/UMTS (WCDMA/FDD) and Quad Band 2G GSM. A powerful Java® embedded system enables fast and easy application development. It can simultaneously host and run multiple applications and supports free firmware updates over-the-air (FOTA) when required.

The Cinterion mPLS8 Modem Card offers worldwide coverage and GPS. It delivers Penta Band LTE, Tri-Band UMTS/WCDMA and Dual-Band GSM/GPRS/EDGE. Two antenna pads enable diversity support for improved data speeds, and an optimized GPS antenna path eliminates blanking for more consistent performance.

The Cinterion mPLAS9 LTE Modem Card delivers eleven Band LTE Advanced, Quad-Band LTE-Advanced TDD plus 2G / 3G fallback for global coverage. It features an innovative RF concept for extreme performance, enhanced sensitivity and connection stability. It enables carrier aggregation for enhanced peak data rates and optimized use of spectrum for improved connectivity performance.

Cinterion Modem cards are ideal for any IoT application that encompasses the commonly used 52-pin express connector in its product design. The cost effective LTE Modem Cards deliver industrial quality and rugged durability while eliminating the need for soldering in small and mid-sized projects.


Industrial Plus Family Benefits

Cinterion Modem Cards feature proven IoT modules from the Industrial Plus product family, which leverage the latest wireless standards to deliver IoT optimized data speeds and Multi Band capabilities for seamless global coverage.


The Modem Cards provide seamless migration to next generation products within in the family to protect your IoT investment. Like all Cinterion products, they come with full type approval (FTA) and they are certified by the largest global network operators. All Cinterion connectivity products are compatible with Gemalto's comprehensive suite of solutions, services and platforms that help enterprises Connect, Secure and Monetize IoT technology.

Instant LTE with Multi Band Cat 1, Cat 3 and Cat 6 Connectivity

mPLS8 & mPLS62-W



mPLAS9



Instant Plug and Play Access to LTE Networks

Cinterion LTE Modem Cards quickly plug into existing 52-pin express sockets card slots to provide instant access to cellular networks for any industrial IoT application.

Complete and Seamless Global IoT Connectivity

The suite of LTE Modem Cards deliver a complete global approach to instant IoT connectivity providing Multi Band LTE, Multi Band 3G HSPA/UMTS and Quad Band GSM for seamless coverage and roaming across different wireless networks.

IoT Optimized Power Management

An advanced power management system ensures Modem Card reliability and provides optimized sleep mode to preserve power and extend battery life.

The Gemalto Advantage:

Since 1996, Gemalto has been pioneering market-leading M2M and IoT products that keep our customers on the leading edge of innovation. Unique value added benefits include:

- > Trusted partner to 450+ global MNOs ensures products evolve in sync with networks and modules are pre-certified for all global mobile networks
- > Core competency in MIM, SIM and eUICC technology allows simplified integration with modules and lower Total Cost of Ownership
- > Expert design consulting, local market engineering support and a skilled 24/7 help desk streamline development and deployment
- > Global leader in digital security solutions and platforms
- > Experienced provider of software solutions for Quality of Service and product lifecycle management
- > Extensive RF test capabilities and GCF/PTCRB pretests to validate readiness for solution approval process

Cinterion® Modem Cards Features

	MPLS62-W LTE CAT 1 MODEM CARD	MPLS8 LTE CAT 3 MODEM CARD	MPLAS9 LTE CAT6 MODEM CARD
DIMENSIONS	50.95 x 30 x 5.56 mm	50.95 x 30 x 4.7 mm	50.95 x 32.6 x 5.3 mm
OPERATING TEMPERATURE	-40°C to +85°C	-40°C to +85°C	-40°C to +85°C
GENERAL FEATURES	<p>mPLS62-W: 3GPP Release 9</p> <p>Twelve Bands LTE 1, 2, 3, 4, 5, 7, 8, 12, 18, 19, 20, 28</p> <p>Seven Bands UMTS 1, 2, 4, 5, 8, 9, 19</p> <p>Four Bands GSM: 850, 900, 1800 and 1900 MHz</p>	<p>mPLS8-US Variant: Four Bands LTE 2, 4, 5, 17 Three Bands UMTS 2, 4, 5 Four Bands GSM 850, 900, 1800 and 1900 MHz</p> <p>mPLS8-E Variant: Five Bands LTE 20, 8, 3, 1, 7 Three Bands UMTS 8, 3, 1 Two Bands GSM 900, 1800 MHz</p>	<p>mPLAS9-X Variant: Seven LTE-Advanced FDD 12, 13, 17, 29, 5, 4, 2 Three Bands UMTS 2, 4, 5 Four Bands GSM 850, 900, 1800 and 1900 MHz</p> <p>mPLAS9-W Variant: Eleven Bands LTE-Advanced FDD 1, 3, 5, 7, 8, 18, 19, 20, 26, 28A/B Four Bands LTE-Advanced TDD 38, 39, 40, 41 Five bands UMTS 5, 6, 8, 3, 1 Two bands GSM 900, 1800 MHz</p>
MODULE SPECIFICATIONS	<p>FDD-LTE Cat.1 DL: max. 10.2 Mbps, UL: max. 5.2 Mbps</p> <p>HSPA+ Cat.8 data rates DL: max. 7.2Mbps, UL: max. 5.76Mbps</p> <p>Full & Incremental Firmware update via USB</p>	<p>LTE Cat. 3 DL/UL max: 100 Mbps / 50 Mbps</p> <p>HSPA+ DL Cat. 24 / UL Cat. 6, Dual Carrier DL/UL max: 42 Mbps / 5.76 Mbps</p> <p>UMTS DL/UL: max. 384 kbps EDGE Class 12 DL/UL: max. 237 kbps GPRS Class 12 DL/UL: max. 85.6 kbps</p> <p>Multiple Operator VoLTE support, CSFB (circuit-switched fallback)</p>	<p>LTE Cat. 6, DL CA up to 40MHz, DL/UL max: 300 Mbps / 50 Mbps HSPA+ Dual Carrier DL Cat. 24 / UL Cat. 6, DL/UL max: 42 Mbps / 5.76 Mbps</p> <p>UMTS DL/UL: max. 384 kbps EDGE Class 12 DL/UL: max. 237 kbps GPRS Class 12 DL/UL: max. 85.6 kbps</p>
SPECIAL FEATURES	<p>USB Interface features a composite mode, compliant to Windows, Linux and Mac</p> <p>Firmware update via USB RLS Monitoring (Jamming detection) Informal Network Scan Cell ID based Location Support</p>	<p>2x2 DL-MIMO support RX diversity support Integrated GPS / GLONASS / GALILEO solution Multiplexer according to 3GPP TS 27.010 USB interface supports multiple composite modes and a Linux-/Mac- compliant mode Full & Incremental Firmware update via USB</p>	<p>Intra-Band-Contiguous and Inter-Band Carrier Aggregation (CA) in Downlink (DL)</p> <p>2x2 DL-MIMO support</p> <p>Antenna diagnostics</p>
REGULATORY APPROVALS*	CE, GCF, RED, FCC, PTCRB, RoHS, REACH	RED, GCF, FCC, PTCRB, UL, IC, CE, RoHS, REACH and Regulatory approvals	CE, GCF, RED, RoHS, REACH
DRIVERS	<p>USB, MUX driver for Microsoft® Windows®</p> <p>RIL Driver for Android</p> <p>RIL, USB driver for Microsoft® Windows Embedded Handheld™</p>	<p>NDIS USB, MUX driver for Microsoft® Windows®; Microsoft Windows mobile®</p> <p>Android™ RIL driver USB & MUX driver for Linux®</p>	<p>NDIS USB driver for Microsoft® Windows®</p> <p>Android™ RIL driver USB for Linux®</p>

*) based on module approvals

Connect. Secure. Monetize.™

Gemalto's complementary offering of solutions, services and solid identity management helps enterprises unleash the power of the IoT, providing a solid foundation of Trust based on three key pillars:

- > **Connect.** The backbone of any IoT solution, Cinterion M2M Modules, SIM/MIMs, Terminals and secure services provide future-proof, reliable connectivity for all vertical market IoT solutions.
- > **Secure.** Gemalto's end-to-end security solutions protect devices, the network and the cloud while managing the entire application lifecycle.
- > **Monetize.** Our agile Sentinel monetization solutions enable innovative business models and new revenue streams through embedded licensing, while the secure device-to-cloud platform speeds time to market.

For more information, please visit www.gemalto.com/iot, developer.gemalto.com, blog.gemalto.com, or follow @gemaltoIoT on twitter.

The information provided in this brochure contains merely general descriptions or characteristics of performance, which in case of actual use do not always apply as described or which may change as a result of further development of the products. An obligation to provide the respective characteristics shall only exist if expressly agreed in the terms of contract. All product designations may be trademarks or product names of Gemalto M2M GmbH or supplier companies whose use by third parties for their own purposes could violate the rights of the owners.

➔ GEMALTO.COM/IOT

THALES

gemalto
a Thales company