



802.11ac 3x3 Dual Band High-Powered Wireless Access Point/Client Bridge

The ECB1750 marks a new speed and performance breakthrough for users with 802.11ac laptops and other devices, who need to wirelessly stream HD video or transfer large files. The ECB1750 is an 802.11ac 3x3 Dual Band Indoor Access Point and Client Bridge. This desktop or wall mount Dual Band Access Point features speeds up to 1300 Mbps on the 5 GHz band when associated with AC client devices and up to 450 Mbps on the 2.4 GHz band. It can be configured as an Access Point, Client Bridge, or WDS (AP, Station, & Bridge) and features a high transmit RF power of 29 dBm on both frequency bands for long range connectivity. The ECB1750 is a cost-effective solution for hotels, multi-floor corporate offices, schools and universities, small-to-medium sized companies and even larger homes.

When set to Client Bridge mode, Ethernet-enabled devices such as printers and copiers can join a business's existing wireless network when they are connected to the ECB1750's Gigabit Ethernet port, making applications like printing from wireless laptops or tablets even easier. In WDS mode, the ECB1750 enables a company's wireless network to be expanded without a wired connection between devices.

Key Features

- 802.11ac wireless speeds of up to 1300 Mbps on the 5 GHz band
- 802.11n wireless speeds up to 450 Mbps on the 2.4 GHz band
- Up to 29 dBm transmit power per band, enabling long range connectivity
- Fast Roaming protects sensitive delay applications such as Voice and Video from disconnecting
- Three detachable 5 dBi 2.4 GHz Omni-directional antennas
- Three detachable 5 dBi 5 GHz Omni-directional antennas
- Can be monitored after deployment with EnGenius EZ Controller™ software for Windows, Mac OS X and Linux (available as a free download)
- Can be used with included power adapter or via PoE with PoE 802.3at capable switches or injectors
- Dual Band / Three Stream (3x3)
- Band Steering feature detects Dual band clients and shifts them to the 5 GHz band to relieve network congestion on the 2.4 GHz band to maintain optimal data traffic flow
- Supports IPv4/IPv6
- Secured Guest Network option available
- SSID-to-VLAN Tagging




The ECB1750 also features Band Steering that shifts wireless traffic for Dual Band-capable clients to the 5 GHz band from the 2.4 GHz band, which helps to relieve network congestion and maintain optimal throughput speeds.

The ECB1750 supports wireless encryption standards such as Wi-Fi Protected Access (WPA-PSK/WPA2-PSK) Encryption, IEEE 802.1X with RADIUS. MAC Address Filtering is also included allowing network administrators to allow or deny network access to client devices (computers, tablet PCs, NAS, smartphones, etc.) according to their MAC addresses. EnGenius' EZ Controller™ Management Software for Windows, Mac OSX, and Linux

(available as a free download) allows monitoring, management, and sequential firmware upgrades of EnGenius Access Points that have already been deployed in the network from the convenience of a desk.

The ECB1750's external MIMO antenna array is comprised of three (3) detachable 5 dBi high gain antennas for the 2.4 GHz radio and three (3) detachable 5 dBi high-gain antennas for the 5 GHz radio. This combination of high transmit power, enhanced receive sensitivity, and six (6) high gain antennas results in long range connectivity to client devices and in some venues can minimize the number of Access Points necessary for a deployment.



2.4 GHz (450 Mbps)

5 GHz (1300 Mbps)

3 Stream 802.11ac Wireless Speeds on 5 GHz

Up to 1300 Mbps on its 5 GHz for faster file transfers and smoother video streaming.

3 Stream 802.11n Wireless Speeds on 2.4 GHz

Up to 450 Mbps on its 2.4 GHz.

Dual Band operation

- 2.4 GHz and 5 GHz frequency bands for expanded user capacity.
- Greater number of channels available on the 5 GHz frequency spectrum to support higher bandwidth applications like HD video streaming.

Long-Range Coverage with High Output RF Power and High Gain Antennas

- Up to 29 dBm transmit power enables the wireless signal to penetrate floors, ceilings, and walls for greater device connectivity
- Three detachable 5 dBi high gain Omni-directional antennas for 2.4 GHz
- Three detachable 5 dBi high gain Omni-directional antennas for 5 GHz

Supports Separate Mode Configuration per Frequency Band

Choose one of three modes available to the ECB1750 depending on user needs: Access Point, Client Bridge, or WDS (AP, Station, & Bridge).

Simplified Monitoring and Management

For easier monitoring and maintenance after deployment, users can monitor the device remotely with SNMP-based EZ Controller wireless Access Point software for Windows, Mac OSX, and Linux (available online as a free download).

Band Steering


Detects and allows Dual Band capable clients to shift to the 5 GHz band from the 2.4 GHz band, relieving network congestion and maintain optimal data traffic flow.

Fast Roaming

Multiple ECB1750s can also be configured for Fast Roaming when used with a RADIUS server. This means that employees can be constantly connected to the network – whether they are warehouse workers scanning and capturing barcode information, employees on Wi-Fi phone calls while walking to meetings on another part of a building or healthcare professionals capturing patient information on mobile devices.

SSID-to-VLAN Tagging

Can be configured to broadcast up to eight (8) SSIDs per frequency band. Each SSID can be tagged to a specified company network VLAN for different user access based on established access rights.




Band Steering (Available on Dual Band Products)

How Band Steering Works and Its Benefit


When wireless networks experience excessive traffic, users may be inconvenienced by slower file transfers and frequent video buffering especially on the 2.4 GHz band. Several of the Electron Series Access Points include a Band Steering option which when applied in the browser-based interface, automatically shifts the

connection of Dual-Band client computers, tablets, smart phones and other devices to the 5 GHz band where there is less traffic and more available RF channels. This leaves Single-Band 2.4 GHz (802.11b/g/n) clients to operate in the 2.4 GHz band that with Band Steering activated becomes less congested.

Band Steering: OFF



Band Steering: ON



● 2.4 GHz Band

● 5 GHz Band

Specifications

Standards

IEEE802.11a/n/ac on 5 GHz

IEEE802.11b/g/n on 2.4 GHz

IEEE802.3at

Transmit Power

2.4 GHz up to 29 dBm

5 GHz up to 29 dBm

Antenna

6 External Antennas

3 x Detachable 5 dBi 2.4 GHz Omni-directional Antennas

3 x Detachable 5 dBi 5 GHz Omni-directional Antennas

Physical Interface

1 x 10/100/1000 Gigabit Ethernet Port - IEEE802.3at PoE Input

1 x Reset Button

LED Indicator

Power

LAN

2.4 GHz

5 GHz

Power Source

DC Input: 12VDC/2A

PoE: Compatible with 802.3at

Operation Modes

Access Point

Client Bridge

WDS AP

WDS Bridge

WDS Station

Security

WEP Encryption (64/128/152 bit)

WPA/WPA2 Enterprise (WPA-PSK using TKIP or AES)

Hide SSID in beacons

MAC address filtering, up to 50 MACs

Wireless STA (Client) connection list

Https Support

SSH Support

QoS (Quality of Service)

Complaint on IEEE 802.11e Standards

Management

Auto Channel Selection

Multiple SSID: 16 SSIDs, 8 SSIDs per Radio

BSSID

SNMP V1/V2c/V3

MIB I/II, Private MIB

VLAN Tag/VLAN Pass-through

Clients Statistics

Fast Roaming

RADIUS Accounting

Guest Network

Control

CLI Supported

Multicast Supported

Wi-Fi Scheduler

802.1X Supplicant (CB Mode)

Multicast Supported

Wi-Fi Scheduler

Environmental & Mechanical

Temperature Range

Operating: -32 to 122°F / 0 to 50°C

Storage: -4 to 140°F / -20 to 60 °C

Humidity (non-condensing)

Operating: 90% or less

Storage: 90% or less

Physical Security

Kensington Security Slot

Weights & Measures

Weight: 1.20 lbs. (544.31 g)

Length: 7.44" (189 mm)

Width: 5.51" (140 mm)

Height: 1.02" (26 mm)

Warranty: 1 Year

Package Contents

ECB1750 802.11ac 3x3 Dual Band Indoor Access Point/Client Bridge

3 Detachable 5 dBi 2.4 GHz Omni-directional Antennas

3 Detachable 5 dBi 5 GHz Omni-directional Antennas

RJ-45 Cable

Power Adapter (12V/2A)

Wall Mount Kit

Quick Installation Guide

Maximum data rates are based on IEEE 802.11 standards. Actual throughput and range may vary depending on many factors including environmental conditions, distance between devices, radio interference in the operating environment, and mix of devices in the network.

EnGenius Technologies | 1580 Scenic Ave. Costa Mesa, CA 92626

Email: partners@engeniustech.com | Phone: 888-735-7888 | Website: engeniustech.com

Features and specifications subject to change without notice. Trademarks and registered trademarks are the property of their respective owners. For United States of America: Copyright © 2016 EnGenius Technologies, Inc. All rights reserved. 10/19/16