Peplink Balance One Advanced Dual-WAN Router for Branch Networking.





One Huge Leap Forward for SMB, and Branch Networking.

The Balance One router with dual-WAN load balancing delivers big-business uptime and speed in an affordable package designed just for SMBs, branch offices, and power users. Featuring:



600Mbps Throughput. **Dual WAN Support.**

Drives data at 600Mbps[#] and keeps connections dependable and fast with automatic balancing and failover between links.



Remote User VPN



Enterprise Features.

Connect remote clients to your private network using L2TP with IPsec, monitor Bandwidth Usage, allocate bandwidth for user groups, and more.



Built-in AP Controller and InControl 2.

Built in AP Controller or InControl 2 cloud management puts you in charge of all connected access points, create and manage custom captive portals.



Eight GbE LAN Ports.

Connect all your devices at high speeds, without complicated setup, compromises, or external switches to buy and maintain.



Simultaneous Dual-Band with 11ac Wi-Fi. (Balance One Only)


Balance One (BPL-ONE) gives you two independent networks that also work together, so all your devices can connect without clashing. Recommended Concurrent Users Per Radio is 60.



Unparalleled Modem Support.

The Balance One's USB port supports more than 250 4G LTE/3G modems used by a variety of carriers worldwide.

Setup, Manage, and Monitor Office Wi-Fi from Your Balance One



Connect Your Home Office with LTE Backup for 100% Uptime



Specifications

specifications		6.3 inches		
Balance One / Balance	One Core	160 mm		
WANInterface	2x 10/100/1000M Ethernet Ports [#] 1x USB Interface	1.2 inches 30 mm		
LAN Interface	8x 10/100/1000M Ethernet Ports [#]			
Wi-Fi Interface	Simultaneous Dual-Band 802.11ac/a/b/g/n Access Point*			
Wi-Fi AP Operating Frequency	2412 – 2472 and 5180 - 5825 MHz*	Balance One (BPL-ONE) Built-in Simultaneous Dual-Band 802.11ac/a/b/g/n Wi-Fi AP with Embedded Antenna		
Router Throughput	600Mbps/400Mbps [#]			
Recommended Users	1-60			
Number of VPN/SpeedFusion Peers 2		 Reset 2x 10/100/1000 8x 10/100/1000 1x USB WAN		
PepVPN/SpeedFusion Throughput	30Mbps	Button Ethernet WAN Ethernet LAN Interface		
Power Input	Device: 12V – 24V DC AC Adapter: AC Input 100V – 240V, DC Output 12V			
Power Consumption	15W (max.)	12V – 24V DC Connector		
Dimension	1.2 x 10.7 x 6.3 inches 30 x 271 x 160 mm (H x W x D)	Balance One Core (BPL-ONE-CORE)		
Weight	1.3 pound 570 grams			
Operating Temperature	14° − 113°F -10° − 45°C	Reset 2x 10/100/1000 8x 10/100/1000 1x USB WAN Button Ethernet WAN Ethernet LAN Interface		
Humidity	15% – 95% (non-condensing)			
Certifications	FCC, CE, RoHS, IC	den III		
Warranty	1-Year Limited Warranty	 12V – 24V DC		
		Connector		

"If the WAN Activation License (BPL-ONE-LC-5WAN) is activated, router throughput will be changed to 400Mbps, both number of WAN and LAN will become 5. *Wi-Fi is available on Balance One (BPL-ONE) only.

Product Ordering Information

	J				
Product Code	802.11ac/a/b/g/n AP	Dual-WAN	PepVPN	SpeedFusion Hot Failover/ SpeedFusion Bandwidth Bonding	
BPL-ONE-CORE	0	٠	•	Feature Add-On (BPL-ONE-LC-SF)	
BPL-ONE	٠	٠	٠	Feature Add-On (BPL-ONE-LC-SF)	
Feature Add-On					
Product Code	Applicable to	Description			
BPL-ONE-LC-SF	BPL-ONE/BPL-ONE-CORE	/BPL-ONE-CORE SpeedFusion bonding license			
BPL-ONE-LC-5WAN	BPL-ONE/BPL-ONE-CORE	BPL-ONE/BPL-ONE-CORE Define LAN 1-3 to WAN 3-5			
PVN-LC-05	BPL-ONE/BPL-ONE-CORE	BPL-ONE/BPL-ONE-CORE Enables up to 5 PepVPN connections			
PVN-LC-10	BPL-ONE/BPL-ONE-CORE	Enables up to 10 PepVPN connections			
PVN-LC-20	BPL-ONE/BPL-ONE-CORE	Enab	Enables up to 20 PepVPN connections		

Features

WAN

USB 4G/3G Modem Support Support for PPPoE, Static IP, DHCP Support for Dynamic DNS services WAN Link Health Check Intelligent Failover Bandwidth Allowance Monitor

LAN

DHCP Server for LAN Clients Extended DHCP Options DHCP Reservation DNS Proxy for LAN Clients Per-Port VLAN

Security

Stateful Firewall DoS Prevention

peplink

^ SpeedFusion is available as an optional add-on

AP Controller AP Controller Support

Wi-Fi Usage Statistics
Complete VPN Solution

PepVPIN/SpeedFusion ^ Site-to-Site VPN Bandwidth Aggregation ^ Hot Failover ^ 256-bit AES Encryption Pre-shared Key Authentication Dynamic Routing L2TP with IPsec VPN Server PPTP VPN Server RADIUS, LDAP Authentication IPsec VPN (Network-to-Network)

Load Balancing

Intelligent Failover Session Persistence Per-Service Load Distribution Multiple Algorithms

Networking

NAT and IP Forwarding Static Routes Port Forwarding Many to One, One to One NAT NAT Pool SIP ALG, H.323 ALG UPnP, NAT-PMP WINS Server

Advanced QoS

User Groups Bandwidth Reservation Individual Bandwidth Limit Application Prioritization By User Groups SIP, HTTPS, VPN QoS Custom Application QoS Web Blocking Blacklist

Captive Portal Support Support for Wired and Wireless LAN Clients Support RADIUS Authentication Time and Usage Quotas on Open Access Mode

Built-in Customizable Splash Page

Device Management

10.7 inches 271 mm

> Web Administrative Interface Command Line Interface InControl Cloud Management Email Notification Active Client & Session Lists Bandwidth Usage Statistics Syslog Service SNMP v1, v2c and v3

Package Content

Balance One/Balance One Core 12V Power Supply

www.peplink.com ©Peplink. All rights reserved.

Ref no.: balance-one-201910-v8