

EH7520 Series



Feature Highlights

- Up to 16 10/100 BASE-T(X) ports and 4 10/100/1000 BASE-T(X) Combo ports
- Up to 8 802.3af or 802.3at compliant PoE ports
- ERPS Ring (recovery time < 20ms @ 40 switches), STP/RSTP for network redundancy
- Remote management over Web browser, Telnet console, serial console, and Windows Utility
- PROFINET v2 Class B compatible
- Provide Generic Station Description file (GSD v2.1) for integration with SIMATIC Step 7
- Support for PROFINET I/O parameters, I/O cyclic data, DCP, DHCP and PROFINET Real-Time

Product Description

The EH7520 Series is a highly reliable and fault-tolerant Industrial Managed PoE Ethernet Switch. It equips up to sixteen 10/100BASE-T(X) RJ-45 ports and up to four 10/100/1000BASE-T(X)/FX RJ-45 and SFP ports. With its high performance switching capacity, EH7520 Series provides network redundant self-recovery mechanism is less than 20ms on full load which allows you to scheme a reliable Ethernet network by building a redundant ring topology as your back-up solution. With a Multifunctional web dashboard, EH7520 Series offers intelligent features such as Quality of service (QoS), Virtual LAN (VLAN), IGMP, Port mirroring and security.

The EH7520 Series is designed for Industrial rugged applications. It equips a 5-pin terminal block to provide dual redundant power inputs with Reverse Polarity Protection and two sets of relay which allows field engineers to build up a stand-alone fault alarm system. Its IP30 housing protection, wide operating temperature of -20 to 70°C and DIN-Rail mounting capacities are liable to do most industrial field applications.

General Specifications

Technology

Standards	IEEE802.3af / 802.3at for Power-over-Ethernet
	IEEE802.3 for 10BASE-T
	IEEE802.3u for 100BASE-T(X) and 100BASE-FX
	IEEE802.3ab for 1000BASE-T(X)
	IEEE802.3z for 1000BASE-X
	IEEE802.3x for Flow Control
	IEEE802.1D-2004 for Spanning Tree Protocol
	IEEE802.1w for Rapid STP
	IEEE802.1Q for VLAN Tagging
	IEEE802.1p for Class of Service
	IEEE8021X for Authentication
	IEEE802.3ad for Port Trunk with LACP
Protocols	IGMPv1/v2, GVRP, SNMPv1/v2c/v3, ICMP, ARP, Telnet, DHCP Client, TFTP, SNMP, SMTP, RMON, HTTP, Syslog, PROFINET, Modbus/TCP, LLDP, IEEE 1588 PTP V2, IPv4, NTP Client, EAP, RADIUS, 802.1x
MIB	MIB II, IF-MIB, SNMPv2 MIB, BRIDGE-MIB, RMON MIB Group 1,2,3,9
Flow Control	IEEE802.3x for Flow Control, back pressure flow control

Switch Properties

Priority Queues	8
Max. Number of Available VLANs	256
VLAN ID Range	VID 1 to 4094
Static IGMP Groups	256
Dynamic IGMP Groups	256
MAC Table Size	16K
Packet Buffer Size	12 Mbit

Interface RJ45

Ports Fiber	10/100/1000BASE-T(X) or 10/100 BASE-T(X) auto negotiation speed
Ports LED	100BASE-FX / 1000BASE-X SFP slot
Indicators	PWR1, PWR2, Alarm, Run, Ring, RingMaster, RJ-45 Link/Speed, SFP Link, PoE
Console	RS232 (RJ45 connector)
Relay Output	2 relay outputs with current carrying capacity of 2A @30VDC
DIP Switches	Ring Control
Button	Reset Button

Power Management

Input Voltage	9-48 VDC or 18-30VAC for Non-PoE models
	45-57 VDC for 802.3af mode
	51-57 VDC for 802.3at mode
Input Current	Max. 1.5A @ 18VAC
	Max. 2.0A @ 9VDC (without PD)
	Max. 3.2A @ 45VDC (Support up to 8 ports at 15.4W per PoE port)
	Max. 5.5A @ 51VDC (Support up to 8 ports at 30W per PoE port)
Connector	Removable 5-pin Terminal Block for power input
Reverse Polarity Protection	Present (DC only)

Physical Characteristics

Housing	IP30 protection, metal housing
Dimension	78mm x 137.9mm x 164mm (W x D x H)
Weight	approx 1.4 kg (Max.)
Installation	DIN-Rail, Wall Mount (Optional Kit)

Environmental Limits

Operating Temperature	-20°C~70°C (-4°F~158°F)
Storage Temperature	-40°C~85°C (-40°F~185°F)
Ambient Relative Humidity	5%~95% non-condensing

Regulatory Approvals				
Safety	UL60950-1 2nd Ed. /CSA C22.2 No.60950-1-07 2nd Ed. / EN60950-1 / CB			
EMC	FCC Part 15, Subpart B, Class A / EN 61000-6-4:2007+A1:2011 / EN 61000-6-2:2005			
Test		Item	Value	Level
IEC 61000-4-2	ESD	Contact Discharge	±6KV	3
		Air Discharge	±8KV	3
IEC 61000-4-3	RS	Radiated(Enclosure)	10 (V/m)	3
IEC 61000-4-4	EFT	AC Power Port	±2.0 KV	3
		DC Power Port	±2.0 KV	3
		Signal Port	±1.0 KV	3
IEC 61000-4-5	Surge	AC Power Port	Line-to-Line ±1.0KV	3
		AC Power Port	Line-to-Earth ±2.0KV	3
		DC Power Port	Line-to-Line ±1.0KV	3
		DC Power Port	Line-to-Earth ±2.0KV	3
		Signal Port	Line-to-Earth ±1.0KV	3
IEC 61000-4-6	CS	Conducted(Enclosure)	10 Vrms	3
IEC 61000-4-8	PFMF	(Enclosure)	30(A/m)	4
IEC 61000-4-11	Dip	AC Power Port	-	-
Shock	IEC 60068-2-27			
Drop	IEC 60068-2-32			
Vibration	IEC 60068-2-64			
RoHS	Yes			
MTBF	TBD			
Warranty	5 years			

Ordering Information				
Model Name	Port Interface			
	Fast Ethernet		Gigabit Ethernet	
			Combo Port	
	Non-PoE	PoE	RJ-45	SFP
EH7520-4G-4SFP	16	-	(4)	(4)
EH7520-4G-4PoE-4SFP	12	4	(4)	(4)
EH7520-4G-8PoE-4SFP	8	8	(4)	(4)

Note: Numbers in the parenthesis are the Combo ports.

Optional Accessories	
WMK-450-Black	Metal Wall Mount Kit, Black
CBL-RJ45(8P)-DB9(F)-90-C	8-pin RJ45 to DB9 Female Cross Over Cable, 90cm
AD1120-48F	120W/2.5A DIN-Rail 48 VDC power supply with universal 100~240VAC/120-370VDC input
AD1240-48C	240W/5A DIN-Rail 48 VDC power supply with universal 100~240VAC/120-370VDC input
LM28-C3S-TI-N	SFP Transceiver, 1250Mbps, 850nmVCSEL, Multi-mode, 550m, 3.3V, -20~85°C
LM38-C3S-TI-N	SFP Transceiver, 1250Mbps, 1310nmFP, Multi-mode, 2km, 3.3V, -40~85°C
LS38-C3S-TI-N	SFP Transceiver, 1250Mbps, 1310nmFP, Single-mode, 10km, 3.3V, -40~85°C
LS38-C3L-TI-N	SFP Transceiver, 1250Mbps, 1310nmDFB, Single-mode, 30km, 3.3V, -40~85°C
LM38-A3S-TI-N	SFP Transceiver, 155Mbps, 1310nmLED, Multi-mode, 2km, 3.3V, -40~85°C
LS38-A3S-TI-N	SFP Transceiver, 155Mbps, 1310nmFP, Single-mode, 30km, 3.3V, -40~85°C

Note: Please choose a power supply wisely based on the actual power requirement. EH7520's system require 18W and each PoE port adds 15W for 802.3af or 30W for 802.3at.

ООО «ЕвроМобайл» - официальный дистрибьютор Атор в России, Украине и странах СНГ

ЕвроМобайл Россия

Санкт-Петербург, пр. Энгельса, д. 71, оф. 313
+7 (812) 331-75-76, 8 800 555-75-76
www.euromobile.ru
info@euroml.ru

ЕвроМобайл Украина

Запорожье, пл. Инженерная, д. 1
Тел./факс: +380 (61) 213-41-77
www.euromobile.com.ua
info@euroml.com.ua

